

## COMPACT FLOOR CONSOLE

Set Code			SET-AGTV09LAC	SET-AGTV14LAC
Model No.	Indoor unit		AGTV09LAC	AGTV14LAC
	Outdoor unit		AOTV09LAC	AOTV14LAC
Operation Type			Reverse Cycle	Reverse Cycle
Power Supply	V / Ph / HZ		240 / 1 / 50	240 / 1 / 50
Capacity	Cooling	kW	2.60 (0.90-3.50)	4.20 (0.90-5.00)
	Heating	kW	3.50 (0.90-5.50)	5.20 (0.90-8.00)
Input Power	Cooling (Max)	kW	0.60 (Max 1.40)	1.22 (Max 1.95)
	Heating (Max)	kW	0.81 (Max 2.20)	1.44 (Max 3.05)
EER	Cooling	kW / kW	4.33	3.44
COP	Heating	kW / kW	4.32	3.61
AEER	Cooling	kW / kW	4.102	3.369
ACOP	Heating	kW / kW	4.341	3.552
Star Rating	Cooling		3.5	2
	Heating		3.5	2.5
Running Current	Cooling / Heating	amps	2.8 / 3.8	5.3 / 6.1
Moisture Removal		l / hr	1.3	2.1
Noise Level	Indoor Sound Pressure (High / Quiet)	Cooling	dB(A)	40 / 22
		Heating	dB(A)	40 / 22
	Outdoor Sound Pressure (Cooling / Heating)		dB(A)	47 / 48
	Outdoor Sound Power		dB(A)	64
Air Circulation (Indoor - High Fan) Cooling / Heating		l / sec	158 / 167	181 / 181
Net Dimensions HxWxD	Indoor Unit	mm	600 x 740 x 200	600 x 740 x 200
		kgs	14	14
	Outdoor Unit	mm	540 x 790 x 290	540 x 790 x 300
		kgs	36	40
Piping Connections (Liquid / Suction)		mm	Ø6.35 / Ø9.52	Ø6.35 / Ø12.70
Max Pipe Length (Precharged Length)		m	20 (15)	20 (15)
Max Height Difference		m	15	15
Operation Range	Cooling	°CDB	-10 to 43	-10 to 43
	Heating	°CDB	-15 to 24	-15 to 24
Refrigerant			R410A	R410A

Due to ongoing research and development, specifications and designs are subject to improvement without notice therefore relevant manuals must be consulted before any action is taken to install or service these products.